

SECTION 1: Identification of the substance/mixture and of the company

1.1. Product

Product name : Speed Spray65 : Not
Product code available

1.2. Relevant identified uses

Use of the substance/mixture : Adhesive used for interior installation of flooring material over approved subfloors. Glue-down installation of approved Luxury Vinyl Tile, Luxury Vinyl Plank, Carpet Tile, and Cushion.

1.3. Provided by

Metropolitan Hardwood Floors
8106 S 216th Street
Kent, WA - USA
T 800-851-7056
techserv@metrofloors.com

Metropolitan Hardwood Floors
811 Cliveden Avenue
Delta, BC V3M 5R6
T 800-992-3163
techserv@metrofloors.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Gases under pressure - Dissolved gas

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated.
Precautionary statements (GHS-US) : Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS-US)

None.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|--------------------|--------------------|---------|------------------------------|
| 1,1-Difluoroethane | (CAS No) 75-37-6 | 10 - 30 | Flam. Gas 1 Liquefied gas |

Speed Spray65

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120°F. Do not pierce or burn, even after use. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep locked up and out of reach of children. Keep from freezing. Store away from direct sunlight or other heat sources. Store in dry, cool, well-ventilated area.

Speed Spray65

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| 1,1-Difluoroethane (75-37-6) | |
|------------------------------|----------------|
| ACGIH | Not applicable |
| OSHA | Not applicable |

8.2. Exposure controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Hand protection | : Wear suitable gloves. |
| Eye protection | : Safety glasses or goggles are recommended when using product. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Maintain levels below community environmental protection thresholds. |
| Other information | : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------|
| Physical state | : Gas/Pressurized Liquid |
| Appearance | : Clear |
| Color | : White |
| Odor | : Sweet |
| Odor threshold | : No data available |
| pH | : 5.5 - 7.5 |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Not flammable |
| Vapor pressure | : No data available |
| Relative vapor density at 68°F | : > 1 (Air = 1) |
| Relative density | : 1.03 |
| Solubility | : Miscible |
| Partition coefficient: n-octanol/water | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available.

Speed Spray65

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Oxidizers. Nitrates. Chlorine bleach.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

| Speed Spray65 | |
|---------------------|-------------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rat | No data available |
| LC50 inhalation rat | No data available |

| 1,1-Difluoroethane (75-37-6) | |
|------------------------------|--------------------------|
| LC50 inhalation mouse | 977 g/m ³ /2h |

| | |
|--|---|
| Skin corrosion/irritation | : Based on available data, the classification criteria are not met. |
| Serious eye damage/irritation | : Based on available data, the classification criteria are not met. |
| Respiratory or skin sensitisation | : Based on available data, the classification criteria are not met. |
| Germ cell mutagenicity | : Based on available data, the classification criteria are not met. |
| Carcinogenicity | : Based on available data, the classification criteria are not met. |
| Reproductive toxicity | : Based on available data, the classification criteria are not met. |
| Specific target organ toxicity (single exposure) | : Based on available data, the classification criteria are not met. |
| Specific target organ toxicity (repeated exposure) | : Based on available data, the classification criteria are not met. |
| Aspiration hazard | : Based on available data, the classification criteria are not met. |
| Symptoms/injuries after inhalation | : May cause respiratory tract irritation. |
| Symptoms/injuries after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/injuries after eye contact | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. |
| Symptoms/injuries after ingestion | : Not a normal route of exposure. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

| Speed Spray65 | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| Speed Spray65 | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

No additional information available.

Speed Spray65

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. Pressurized container: Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols, non-flammable

Department of Transportation (DOT) Hazard Classes : 2.2

Hazard labels (DOT) :



Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

15.2. US State regulations

Speed Spray65

| | |
|----------------------------|------|
| State or local regulations | None |
|----------------------------|------|

SECTION 16: Other information

Date of issue : 03/03/2022

SDS created by : Spray-Lock, Inc.

Disclaimer: Product manufactured exclusively by Spray-Lock, Inc. for Metropolitan's Pro Series Speed Spray65. Original SDS prepared on 3/3/2022 by Spray-Lock, Inc. and provided to Metropolitan for use on 3/03/2022. Spray-Lock, Inc. believes the data set forth herein is accurate as of the date hereof.

31-SDS-MHF-3113954
DATE: 03/03/2022
REV: REL