



PRO SERIES

AMB 2000 UNDERLAY SYSTEM

FOR USE WITH:

- Engineered hardwood
- Luxury Vinyl
- Laminate
- WPC/SPC without attached pad
- Carpet Tile

Fire Test ASTM E662:

Smoke Generation Max.
Spec. Optical Density
of 450 or less

Fire Test ASTM E648:

Critical Radiant Flux.045 m²
or greater Class 1

Nominal

Thickness: .070"

Density: 54.93 lb3/ft3

Made with PFI materials
and tests to CA 01350
for indoor air quality.

2 ROLL SIZES:

Width: 6' (1.83M)

Length: 65.62' (20M)

Weight: 4.16 oz ft²

Quantity/Roll: 393.96 ft²

SKU: 3119662

Width: 2.95' (.9M)

Length: 32.8' (10M)

Weight: 4.16 oz ft²

Quantity/Roll: 96.88 ft²

SKU: 3112439

PRO SERIES

AMB 2000 UNDERLAY SYSTEM



NOISE SUPPRESSION



CUSHIONING



MOISTURE BARRIER



METROPOLITAN
SINCE 1992

For Sales Support, contact your local Metropolitan Representative
For Technical Support, please email techserv@metrofloors.com


METROPOLITAN
SINCE 1992



AMB 2000 Underlay System for engineered hardwood, laminate, vinyl, carpet tile and WPC /SPC saves **time, energy and budget**. A high performance 1.8mm underlay floor prep system that floats over the subfloor avoiding costly doublestick installations. **AMB 2000** is your moisture vapor barrier, cushioning and **noise suppression** (thankfully) solution in one easy-to-use product.

AMB 2000 BENEFITS



LESS ADHESIVE
AMB 2000 underlay floats, flooring is adhered to **AMB 2000** reducing adhesive usage by 50% or more.



NOISE SUPPRESSION
AIRC 60 / Delta AIRC 26. Results obtained using 8" concrete sub-floor with no ceiling and Evoke Anchor - 2mm LV. Results will vary depending upon structure and floor/ceiling assemblies.



BLOCKS MOISTURE
Suppresses moisture migration to the flooring system from the top surface of concrete for internal relative humidity levels to 100%.



SECURE + STABLE
Includes a fiberglass core for stability and an embossed back-layer which reduces potential movement of flooring system.



REUSE/RECYCLE
Can be reused in most situations, facilitates simple board replacements (depending on install method) and is recyclable. Eliminates the need to remove most existing flooring saving the cost of demo/removal.



ISOLATES SUBFLOOR
Self-healing, indent-resistant technology is combined to reduce foot, leg and back fatigue by increasing cushioning underfoot.

ESSENTIALS



MST SINGLE-SIDED TAPE
For installations of Hardwood, Laminate & Vinyl Composite flooring. (Required for moisture warranty).

MST DOUBLE-SIDED TAPE
For installations of Luxury Vinyl, and Carpet Tile installations. (Required for moisture warranty).



ADHESIVE
Pro Series 4510 Releasable Adhesive for installing some LVT floors
Pro Series 4584 Premium Vinyl Adhesive for installing LVT floors
Pro Series 3089 Urethane Adhesive for installing engineered hardwood floors
Ever bond Super PSA Adhesive for installing some LVT floors
Pro Series MS+ – Advanced Wood Flooring Adhesive