







**Pro Series MS+** keeps you firmly grounded with both its price and performance. It was created to offer an alternative to traditional urethane-based adhesives. With its early grab, fast-curing formula and tenacious bond, Pro Series MS+ reduces project time and labor accompanying most wood flooring installations.

## 90%\* MOISTURE VAPOR BARRIER ELASTOMERIC WOOD FLOORING ADHESIVE



\*90% RH as it relates to moisture vapor emission rate (MVER) is only applicable when using a moisture / sound control trowel. \*\*Acoustical performance details are the result of tests conducted in accordance with ASTM E 2179-03 (2009) under laboratory conditions. Actual results may vary.



Tech Service: techserv@metrofloors.com Customer Service: USA: 1.800.851.7056 Canada: 1.800.992.3163 Website: www.metrofloors.com

MS+ FLOORING

**PRO SERIES** 

## **PRO SERIES BENEFITS**

- Extremely low odor
- Modified Silane
- High Strength, waterproof bond
- Non-staining and easy to clean
- Wet-set, early grab, fast-curing adhesive formula
- LEED compliant low emitting flooring adhesive
- IIC 66 / STC 61 Delta IIC (ΔIIC) 21\*\*

## **APPROVED FLOORING TYPES**

Engineered and solid hardwood, bamboo, dry-back parquet, cork flooring, cork underlayment, cork-backed hard surface, acrylic impregnated plank, crumb rubber flooring/underlayment.

## **COVERAGE RATE**

50 – 70 sf/gallon dependent upon substrate composition and porosity, application method & flooring type.

Please refer to TDS for more information on trowel types and coverage rates.



For detailed installation guidelines, approved substrates, proper substrate preparation, technical data sheets, safety data sheets, and warranty information please visit: metrofloors.com/metro/ accessories.

