



PRO SERIES Speed Spray 65

Spray Adhesive
For Approved LVT, LVP, Carpet Tile,
Underlayment & More



EPA TEST METHOD 8260B



CERTIFIED BY
SCS Global Services



PRODUCT CHARACTERISTICS

Speed Spray 65 is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank, Carpet Tile, Underlayment and more in commercial and residential applications.

Speed Spray 65 uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. The instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

Speed Spray 65 is a 0.0 g/ml VOC product that allows occupation of the space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.0 g/ml VOC content
- Water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

Speed Spray 65 bonds approved LVT, LVP, Carpet Tile, Underlayment and more to the following properly prepared, smooth, flat, and dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

Speed Spray 65 provides immediate shear strength after installation, allowing instant access to finished floor.

Speed Spray 65 is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Speed Spray 65 uses non-ozone depleting HFC propellant.

Speed Spray 65 is warrantied up to 98% RH, 8 lbs MVER, and 11 pH.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	4 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.0 g/ml per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 98% RH, 8 lbs/1,000 ft ² /24 hr, and 11pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

LVT, LVP, CARPET TILE, UNDERLAYMENT and MORE

150-185 ft² (14-17.2 m²)