



PRO SERIES



APPLICATION:

For approved residential, commercial flooring and underlay.

PRODUCT FEATURES:

- Fast application
- Allows all traffic immediately on Evoke Luxury Vinyl installs/ allows occupation of the space as soon as installation is complete
- Uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive
- Contributes to good indoor air quality: Floorscore Certified and CA Section 01350 compliant
- Water based adhesive
- Non-Flammable
- No offensive odors
- Uses non-ozone depleting HFC propellant
- Easy water clean up while adhesive is still wet

COVERAGE GUIDE:

Heavy Spray Method recommended for Evoke Luxury Vinyl and other flooring material = 150-185 sqft (14-17.2 m²)

Lite Spray Method recommended for bonding AMB 2000 to substrate = 300-375 sqft (27.8-35.8 m²)

KENTWOOD INSTALLTIONS:

- Use Speed Spray65 to bond AMB 2000 to the substrate
- Use Timber Bond Pro to bond Kentwood to AMB 2000

Advantages of Using Speed Spray65 & AMB 2000


- A**-Excellent Acoustical properties
- M**-Cost effective Moisture control on, below, or above grade
- B**-Cost effective underlay eliminating, in many cases, costly grinding, priming, and skim coating, creating a great Bonding surface.

Use Speed Spray65 and AMB 2000 to build installation systems that cut vapor control material and installation costs.

AMB 2000 is a high-performance commercial grade high density acoustical underlay providing up to 100% RH moisture control and a premium bonding surface for multiple flooring types.

When Speed Spray65 is used to bond AMB 2000 to an approved substrate, most projects are ready for foot traffic immediately after flooring installation.

Both Speed Spray65 and AMB 2000 are CA 01350 compliant, the standard used by LEED for products contributing to good indoor air quality. Speed Spray65 is FloorScore certified and AMB 2000 is GREENGUARD Gold certified.



AMB 2000 SKU #3115174

Thickness: .070"

17.78 mm

Dimensions: 6' w x 65.62'

1.83 m x 20 m

Quantity/Roll: 393.96 sqft 36.6 m²

PRO SERIES SPEED SPRAY65

Formulated for Evoke glue-down Luxury Vinyl, Pro Series Speed Spray65 is a versatile adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank, Carpet Tile, Underlayment and more in commercial and residential applications. Speed Spray65 adhesive may also be used in a double stick installation with Pro Series AMB 2000.

APPROVED FOR THE FOLLOWING USES:

- Bond Evoke Luxury Vinyl flooring to approved substrates
- Bond Evoke Luxury Vinyl flooring to AMB 2000
- Bond AMB 2000 to approved substrates

PHYSICAL PROPERTIES

- Water-based acrylic blend

APPROVED SUBSTRATES:

Bonds approved LVT, LVP, Carpet Tile, Underlayment and more to the following properly prepared, smooth, flat, and dust free substrates, such as:

- Metal
- Concrete
- Gypsum
- Underlayment grade plywood



METROPOLITAN
SINCE 1992

Customer Service: USA: 1.800.851.7056 | Canada: 1.800.992.3163

Tech Service: techserv@metrofloors.com

metrofloors.com



3122283